

12. External Programs

1. 在 `test` 目录下新建一个 `test.sh` 文件，并添加以下代码：


```
#!/bin/bash
echo "Hello World!"
which tr
grep expr cut
```

```
root@kali:~# cat /etc/passwd | grep root
```

```
$ grep "^${USER}:" /etc/passwd | cut -d: -f5
```

Steve Parker

1 2 3 4 5 6 7 8 9 10 :

```
$ MYNAME=`grep "^${USER}:" /etc/passwd | cut -d: -f5`  
$ echo $MYNAME  
Steve Parker
```

.

```
#!/bin/sh
find / -name "*.html" -print | grep "/index.html$"
find / -name "*.html" -print | grep "/contents.html$"
```

\square $\square\square\square$ $\square\square\square\square$ \square $\square\square\square$ $\square\square$ $\square\square$ \square $\square\square\square$, \square \square $\square\square\square\square$ $\square\square\square\square$! \square $\square\square$ $\square\square\square\square$:

```
#!/bin/sh
HTML_FILES=`find / -name "*.html" -print`
echo "$HTML_FILES" | grep "/index.html$"
echo "$HTML_FILES" | grep "/contents.html$"
```

[illegible]

 14

 .

Revision #1

Created 17 January 2024 04:15:55 by [redacted] (MeatDumpling)

Updated 17 January 2024 04:16:07 by [redacted] (MeatDumpling)